

# Taste Master® High-Flow Point-of-Use Purifiers

## Typical Taste Master® Purifier Housing



Filtrine's popular drinking water purification system, contained in a 16ga durable, long-lasting stainless steel housing includes an easy-to-change carbon block element. All the benefits of high-flow filtered water are available at any potable water outlet.

## The High-Flow Taste Master element features include:

- Reduced pressure drop through the element
- Increased surface area for a more efficient filtration
- Combination particulate/carbon element reduces the need for a pre-filter

## 1 MICRON CARBON BLOCK ELEMENT

Meets NSF/ANSI Standards 42 and 53 for:

- Sediment particles down to 1 micron
- Organic taste and odor
- Chlorine taste and odor


## EXCLUSIVE "DUAL-SEAL" ELEMENT DESIGN

Conventional cartridge-type filters depend upon compression of the cartridge top and bottom to effect a seal. When wet the average cartridge loses some rigidity, making it impossible to stop water from bypassing the element.

Filter and purifier elements do not rely on cartridge compression. Filtrine's exclusive "Dual-Seal" design ensures first-day effectiveness for the life of the element.

## Typical High-Flow Taste Master® Element

### Section View




## PURIFIER INSTALLATION

- Allow clear space under purifier to facilitate element change (see page 2)
- Water line temperature should be a maximum of 125 °F and a maximum pressure of 150 psi


## PURIFIER MAINTENANCE

- Replace element every 4 months or *more often if required*


## Typical Undersink Installation



## High Flow-Rate Models Can Serve Multiple Outlets



## Typical Purifier (For other sizes see tables below)



## 1 MICRON TASTE MASTER PURIFIERS

MODEL NO.	FLOW (GPM)	HOUSING				ELEMENTS			
		MODEL NO.	BOM NO.	H (INCH)	CONN IN/OUT	MODEL NO	BOM NO.	L (INCH)	CLEARANCE BELOW HOUSING FOR SERVICE (INCH)
TMS1-1.0	2	TMS1	46.0897	8 $\frac{1}{2}"$	$\frac{3}{4}"$ FPT	TMS1-5-1.0-HF	46.2641	4 $\frac{1}{2}"$	6"
TMS2-1.0	5	TMS2	46.0898	13 $\frac{1}{2}"$	$\frac{3}{4}"$ FPT	TMS2-10-1.0-HF	46.2642	9 $\frac{1}{2}"$	6"

**NOTE :** Clean filter pressure drops 5psi at the rated flow. Consult factory when in-coming water has high turbidity or low pressure.

Water line temperature a maximum of 125°F and a maximum pressure of 150 psi.