



FOUNTAIN SPECIFICATIONS

FILLING STATION MATERIAL – 16 gauge

- ☐ Stainless Steel ☐ Bronze
- FINISH**
- ☐ Satin ☐ Mirror ☐ Statuary Bronze
- ☐ Oil Rubbed Bronze ☐ Powder Coat

COVER PLATE MATERIAL – 16 gauge

- ☐
- Stainless Steel
- ☐
- Bronze

FINISH

- ☐ Satin ☐ Mirror ☐ Statuary Bronze
☐ Oil Rubbed Bronze ☐ Powder Coat

FILLING STATION "SOFT TOUCH" PUSH BUTTON
ADA compliant, less than [5] lbs force to activate

MATERIAL

- ☐
- Stainless Steel
- ☐
- Bronze

FINISH

- ☐ Satin ☐ Mirror [S] ☐ Statuary Bronze
☐ Oil Rubbed Bronze ☐ Powder Coat

FOUNTAIN BUBBLER TYPE

- ☐ Integral "PUSH BUTTON" valve
- ☐ Separate "SOFT TOUCH" button valve [S]
- ☐ Integral "EASY TOUCH" lever valve
- ☐ Separate "SIDE MOUNT" lever valve

FOUNTAIN BUBBLER MATERIAL

- ☐
- Stainless Steel
- ☐
- Bronze

FINISH

- ☐ Satin ☐ Mirror [S] ☐ Statuary Bronze
☐ Oil Rubbed Bronze

FOUNTAIN LOCATION

- ☐
- Right
- ☐
- Left

VANDAL-PROOF BUBBLER – OPTION

- ☐ Tamper-resistant set screw secures bubbler to fountain

"HANDS-FREE" PHOTOCELL ACTIVATION – OPTION

Includes [4] AA lithium batteries with approximately 400,000 activation cycles. Features automatic shutoff [30 second] – helps prevent vandalism and water waste.

- ☐
- On fountain
- ☐
- On filling station

CHILLER SPECIFICATIONS

MODEL: 56A – WATER IN: 1/4" FPT

COOLING CAPACITY: 6 gph at 50°F

STORAGE: 2 gal, insulated, stainless steel tank

REFRIGERANT: HFC R134a "Ozone Safe"

ELECTRICAL: 115/60/1 or [specify]

PURIFIER SPECIFICATIONS

MODEL – TasteMaster TMS1-0.5

CONSTRUCTION – Stainless Steel outer housing

ELEMENT – Carbon block removes particulates, cysts, chlorine, organic odors and tastes. Exclusive "Dual Seal" design negates bypassing and leaking.

[S] = STANDARD

FCC-B103-107-14 Installation Instructions

