



# FCC-B103-HC FILLING STATION With Chiller/Purifier & Hot Water



FCC-B103-HC FILLING STATION  
*Illustration*

### FILLING STATION OPTIONS

STAINLESS STEEL INTERIOR FINISH  
 Satin  Powder Coat

STAINLESS STEEL FRONT PANEL FINISH  
 Satin  Mirror  Powder Coat

BRONZE FRONT PANEL FINISH  
 Satin  Mirror  
 Statuary  Oil rubbed

### "SOFT TOUCH" BUTTON FILLER VALVE

ADA compliant - less than 5 lbs force to activate

STAINLESS STEEL "SOFT TOUCH" BUTTON FINISH  
 Mirror [S]  Satin  Powder Coat

BRONZE "SOFT TOUCH" BUTTON FINISH  
 Satin [S]  Mirror  
 Statuary  Oil rubbed

### "HANDS-FREE" PHOTOCELL ACTIVATION

Includes [4] Lithium AA batteries – approx. 400,000 activation cycles. 30 sec. automatic shutoff to prevent vandalism and water waste

### DIGITAL BOTTLE COUNTER

Encourage use of filling station to refill consumer's own bottle  
*Only available with "HANDS FREE" OPTION*

### RECOMMENDED INSTALLATION

- FILLING STATION with "Soft Touch" button filler valve at 48" maximum for ADA compliance
- Use unit's vertical mounting points for proper installation

### PURIFIER SPECIFICATIONS

MODEL: TasteMaster TMS1-0.5  
 HOUSING: Stainless Steel outer housing  
 ELEMENT: Carbon block removes particles, cysts, chlorine, organic odors and tastes. Exclusive "Dual Seal" design negates bypassing and leaking.

### CHILLER MODEL: 86A

COOLING CAPACITY: 9 gph at 50°F  
 STORAGE: 2 gal, insulated stainless steel tank  
 REFRIGERANT: HFC R134a "Ozone Safe"  
 ELECTRICAL: 115/60/1 [STD]

### HEATER SPECIFICATIONS

MODEL: CC-171 [ETL LISTED]  
 CAPACITY: Approx. 72 fl oz  
 CONSTRUCTION  
 Storage Tank: stainless steel  
 Housing: enameled aluminum  
 ELECTRICAL  
 500W [4 AMP] - 110-120/60/1  
 With 6 ft cord and grounded wall plug

[S] = STANDARD / [O] = OPTIONAL

## FCC-B103-HC FILLING STATION WITH CHILLER/PURIFIER & HOT WATER HEATER

WALL OPENING  
 19"W x 13-1/2"D x 49"H

