



OPTIONS

- HIGH AMBIENT**
Oversized condenser supplies full capacity in ambient temperatures up to 120°F [48.8°].
- SPECIAL ACCESSORIES**
Includes water jug filler, eye wash fountain, lifting eyes and key lock on service panel.
- TASTE MASTER® TMS1-0.5 WATER PURIFIER**
Housing: Heavy duty stainless steel
Element: 0.5 micron, biodegradable carbon block removes lead, particulates, cysts, chlorine, organic odors and tastes. Exclusive seal design negates bypassing and leaks.


Filtrine's free standing industrial INDESTRUCT EXPLOSION PROOF DRINKING WATER COOLERS are engineered to meet Class 1, Group C or D, Div. 1 or 2 requirements for hazardous environments.

FEATURES

- 16 gauge steel or stainless steel cabinet on heavy duty angle frame
- Oversized stainless steel cooling tank to meet peak demands and reduce compressor wear
- Removable cooling package insert with built-in bypass allows for repairs without interrupting water service
- Dual "Push Button" bubbler models offer the savings of two coolers in one

SPECIFICATIONS

- **CABINET**
Heavy duty angle frame with removable front panel for complete access to all components. All stainless steel top and corner legs.
16 ga Stainless Steel Panels:
 - Satin Finish [Standard]
 - Powder Coat Finish [Optional]
- **COOLING TANK**
Heavy gauge stainless steel tank tested at 250 psi for 125 psi working pressure with stainless steel immersion coil type evaporator. Tank storage equal to at least 1/2 of recovery capacity to meet all peak demands for drinking and thermos filling at breaks, shift changes, etc. Insulated tank housed in a rust-proofed steel box.
Stainless Steel: 304 [Standard] 316L [Optional]
- **CONDENSING UNIT**
Open type belt driven compressor with explosion-proof motors and electrical enclosures, air or water cooled condenser, charged with HFO R513A "Ozone Safe - Low GWP" refrigerant, automatic controls and freeze-up protection.
- **ELECTRICAL**
Standard: 115 or 220/60/1 or 208-230 or 460/60/3
3 phase or 50 cycle available, consult factory.
- **FIXTURES**
Heavy duty chromed lead-free brass "Push Button" bubbler valves, stainless steel bowls. Gooseneck water bottle fillers [lever valve or push button] may be specified in place of one or both bubblers.
Other fixture options available, consult factory.



INDESTRUCT DRINKING WATER COOLER SPECS/SELECTION CHART								
FILTRINE MODEL NUMBER	GALLONS STORAGE	CAPACITY 80°F-50°F		COMPRESSOR HP	DIMENSIONS - INCHES			SHIPPING WEIGHT LBS
		GPH	PERSONS		W	D	H	
IM-4-XP	4	8	113	1/4	28	17	40	350
IM-7-XP	7	16	200	1/3	29	17	40	400
IM-14-XP	14	22	275	1/2	32	18	40	470
IM-25-XP	25	30	375	3/4	36	24	42	610
IM-40-XP	40	60	750	1-1/2	55	25	42	950

NOTE Water cooled models available, use suffix **-W**. Dimensions and weights may vary due to options installed and model type. Consult factory for exact specs.