

RECIRCULATING LOOP CHILLERS



TYPICAL CHILLER

APPLICATIONS

- | | |
|-------------------|----------------------|
| Jacket Cooling | Computers |
| Lasers | Power Supplies |
| Induction Heaters | Vacuum Ovens |
| Machine Tools | Injection Molding |
| Welders | Plasma Spraying |
| MRI Equipment | Linear Accelerators |
| CAT Scans | Electron Microscopes |

FEATURES

Energy Saving Design

Unlike most process chillers, compressor runs only as needed. Storage design provides close temperature control and safety from freeze-up without constant operation.

Complete Temperature Control

Temperature adjustable within a range of 40° to 90°F [5° to 32°C] and will hold temperature within ±1.5°F [1°C] of setting. [±0.5°F optional]

Welded Stainless Steel Cooling Tank

Recirculates clean coolant sealed from the atmosphere, eliminates bacterial build-up and internal corrosion.

Uses HFC Refrigerant

Eliminates use of ozone-depleting refrigerant as per Montreal Protocol.

Unlimited Options for Any Application

50+ options to meet any special need. See bulletin O & A.

LIFETIME WARRANTY Consult factory for details.

ONE YEAR WARRANTY All parts covered FOB jobsite for [12] months from start-up date or [15] months from date of shipment, whichever comes first. Consult factory for details.

START-UP and FIRST YEAR SERVICE Filtrine can arrange start-up and first year service on all parts and labor. Regular maintenance, to help prevent costly down-time, is available on a contractual basis. Consult factory for details.

ENERGY SAVINGS OPTIONS

ENGINEERED TO REDUCE
CHILLER OPERATING COSTS

Contact Filtrine For Details

MODEL.....PCP or POC-2000S-230

FIELD SERVICEABLE HERMETIC MODELS

DESCRIPTION

Recirculating chillers recirculate a clean coolant at constant temperature and pressure to increase the stability and consistency of water cooled machines and instruments. Air cooled chillers eliminate the use of tap water and prevent clogging and corrosion of small diameter heat exchangers due to rust and scale build-up.

• **PCP - Closed Loop Chillers:** Use a storage type cooling tank, with immersion coil evaporator, to provide close temperature control of recirculating coolants. The tank is sealed to prevent coolant evaporation and fouling, and supplied with a liquid level gauge, fill port and clean out. The pump recirculates coolant at constant pressure and flow, which is adjustable by turning a manual bypass valve.

• **POC - Open Loop Chillers:** Pump liquid from an open tank or sump, through the chiller and back to the sump. An adjustable thermostat senses the make up liquid temperature, cycling the chiller to insure constant temperature in the sump.

SPECIFICATIONS

COOLING CAPACITY: BTU/HR 230,000
Watts 67,409

Rating Conditions

Coolant Discharge Temperature 68°F (20°C)

Ambient Temperature..... 90°F (32°C)

COMPRESSOR: HP 20

Field serviceable semi-hermetic type supplied condenser as specified below, high/low pressure stat, freeze control, head and suction gauges, oil pressure switch, pump down solenoid valve, thermostatic expansion valve, refrigerant sight glass and dehydrator.

STANDARD CONDENSERS (Designated by suffix)

A.....Fan cooled condenser for indoor installation.

AR.....Remote Air cooled condenser furnished separately for mounting on roof.

W.....Water cooled condenser for hookup to city or tower water

A-WP.....Self-contained air cooled condenser; complete unit made weather-resistant for outdoor installation

COOLING TANK & EVAPORATOR: Capacity 130 gal (494 l)

Welded stainless steel shell and immersion coil evaporator.

Tank tested at 250# for 125# working pressure. Supplied with liquid level gauge and insulated with closed cell thermo-elastomer with an R factor of 3.7.

PUMP: HP 2

Capacity 40 gpm (152 lpm) @ 35 psi

Stainless steel centrifugal pump mounted on rubber pads over a stainless steel condensation tray and supplied with unions and service valves and manually adjustable bypass valve. All piping and fittings brass, copper, or bronze and insulated with closed cell thermo-elastomer with an R factor of 3.7.

THERMOSTAT: Adjustable Range 40° to 90°F (5° to 32°C)

Temperature Stability ±1.5°F (1°C)

CABINET: Enameled aluminum panels with stainless steel corner legs and top on a welded angle iron frame. Panels removable for access to all components.

SUPPLY POWER: 208 - 230/60/3 or 460/60/3

FLA Amps Maximum: 75 or 38

NOTE: FLA may vary depending on options. See MCA and MOP ratings on as-built unit.

PLUMBING CONNECTIONS IN & OUT 1-1/2" (38mm) MPT

CHILLER DIMENSIONS & WEIGHTS								
FILTRINE MODEL NUMBER	W		D		H		SHIPPING WT	
	in	cm	in	cm	in	cm	lb	kg
PCP or POC 2000S-230-A	116	294	52	132	80	203	4000	1800
PCP or POC 2000S-230-W	116	294	34	86	60	152		
PCP or POC 2000S-230-AR	116	294	34	86	60	152		
PCP or POC 2000S-230-A-WP	140	365	52	132	80	203		

NOTE: Chiller dimensions and shipping wts. may vary depending on options - confirm with factory.

STANDARD OPERATING CONDITIONS

OUTDOOR AMBIENT
-20° to 100°F (-29° to 38°C)

OPTIONAL OPERATING CONDITIONS


OUTDOOR AMBIENT
Up to 110°F (43°C)
Up to to 120°F (49°C)
Down to -30°F (-34°C)

NOTE Higher ambient options may affect unit dimensions.

REMOTE CONDENSER

Use w/Standard Models - Furnished complete w/controls for operating in ambient temperatures to minus 20°F (-29°C), consult factory for specs. Connections for remote condenser are at right end of chiller cabinet.

STANDARD MODELS: Suffix A, AR, W & A-WP



LEGEND

- | | |
|----------------------|--------------------------------------|
| 1. Air Vent | 7. To Remote Condenser (AR Models) |
| 2. Fill Port | Condenser Water Out (W Models) |
| 3. Coolant Return | 8. From Remote Condenser (AR Models) |
| 4. Coolant Discharge | Condenser Water In (W Models) |
| 5. Control Panel | 9. Electrical Connection |
| 6. Gauges | 10. Channel Skids |

VENTILATION PANELS

Standard models — air intake at rear, air discharge at right end and front on A & WP models. Manufacturer recommends 12 inch minimum clear space opposite all ventilation panels.

REMOVABLE SERVICE PANELS


Front & rear on all models. Manufacturer recommends 36 inch clearance at front for service.

CHANNEL SKIDS

Channel skids project 2" (5cm) front and rear. Allow additional 2" (5cm) to height for channel skids. Center of 5/8" (16mm) mounting holes located 6" (15cm) from chiller end and 1" (2.5cm) from chiller edge front and rear.

NOTE: Drawing is a composite of various models to demonstrate plumbing locations. Confirm footprint with factory.

PUMP CAPACITY					
MODEL*	GPM @ PRESSURE SHOWN				
	psi	10	20	30	40
	ft	23	46	69	92
STD-2C		65	57	46	30
OP-3C		■	■	72	58
* Standard pump is 2HP, centrifugal (C). Optional pumps (OP) are available.					



* For outlet temperatures below 34°F - use appropriate antifreeze

