

ONE-PASS CHILLER



TYPICAL CHILLER SHOWN

APPLICATIONS

Photo Developing
Ingredient Make-up
Poultry Cooling
Bottling
Dispensers
Pharmaceuticals

Reverse Osmosis
Ice Machines
Spray Washes
Beverages
Eye Wash Water
Boiler Feed Samples

FEATURES

Energy Saving Design

Unlike most process chillers, compressor runs only as needed. Storage design provides close temperature control and safety from freeze-up without constant operation.

Complete Temperature Control

Temperature adjustable range of 40°F to 90°F [5°C to 32°C] and will hold temperature within $\pm 2^\circ\text{F}$ [1°C] of setting.

Welded Stainless Steel Cooling Tank

Coolant sealed from the atmosphere, eliminates bacterial build-up and internal corrosion.

Uses HFC Refrigerant

Eliminates use of ozone-depleting refrigerant as per Montreal Protocol.

Unlimited Options

Design the perfect cooling system for any application. Over 50 options to meet almost any special need. Refer to Bulletin O & A.

LIFETIME WARRANTY Consult factory for details.

ONE YEAR WARRANTY All parts covered FOB jobsite for [12] months from start-up date or [15] months from date of shipment, whichever comes first. Consult factory for details.

START-UP and FIRST YEAR SERVICE Filtrine can arrange start-up and first year service on all parts and labor. Regular maintenance, to help prevent costly down-time, is available on a contractual basis. Consult factory for details.

MODEL PC-8000-860

DESCRIPTION

A completely packaged liquid chiller designed for applications where the liquid to be cooled passes through the chiller only once before either being added as an ingredient to a product or fouled by the product it is cooling. It is most important that a one-pass chiller be able to chill liquids at high and low flow rates without significant pressure drop or danger of freeze up, and yet have close, accurate temperature control.

Filtrine PC chillers are specifically designed for one-pass cooling. A high transfer immersion coil evaporator supplies maximum capacity at any flow rate with no pressure drop. Storage tank design permits close temperature control without short-cycling.

SPECIFICATIONS

COOLING CAPACITY

BTU/HR 860,000

Watts 252,052

Rating Conditions

Coolant Discharge Temperature 68°F [20°C]

Ambient Temperature 90°F [32°C]

Flow rate 75 gpm @ 60 PSI [285 lpm]

COMPRESSOR HP DUAL 40

Field serviceable semi-hermetic type supplied with condenser as specified below, high/low pressure stat, freeze control, head and suction gauges, oil pressure switch, pump down solenoid valve, thermostatic expansion valve, refrigerant sight glass, dehydrator and oil separator.

STANDARD CONDENSERS [Designated by suffix]

- W Water cooled condenser for hookup to city or tower water

- AR Remote air cooled condenser for outdoor installation

COOLING TANK & EVAPORATOR

Capacity 510 gal [1938 ltr]

Welded stainless steel shell and immersion coil evaporator.

Tank tested at 250# for 125# working pressure and insulated with closed cell thermo-elastomer with an R factor of 3.7 and enclosed in rust-proof steel jacket.

THERMOSTAT: Adjustable Range 40° to 90°F [5° to 32°C]

Temperature Stability $\pm 2^\circ\text{F}$ [1°C]

CABINET: Enameled aluminum panels and top with stainless steel corner legs. Panels removable for access to all components.

SUPPLY POWER: 208-230/60/3 or 460/60/3

FLA Amps Maximum: 350 or 175

NOTE: FLA may vary depending on options. See MCA and MOP ratings on as-built unit.

PLUMBING CONNECTIONS IN & OUT 3" [70 mm] FPT

SHIPPING WEIGHT SEE CHART ON REVERSE

CHILLER DIMENSIONS and WEIGHTS

FILTRINE Model No.	W		D		H		SHIP WT	
	in	cm	in	cm	in	cm	lb	kg
PC-8000-860-AR	126	320	60	152	90	229	6500	2925
PC-8000-860-W	126	320	60	152	80	229		

NOTE: Chiller dimensions and shipping wts. may vary depending on options - confirm with factory.

LEGEND

- | | |
|--------------------------|--------------------------------------|
| 1. Gauges | 6. To Remote Condenser [AR Models] |
| 2. Control Panel | Condenser Water Out [W Models] |
| 3. Coolant In | 7. From Remote Condenser [AR Models] |
| 4. Coolant Discharge | Condenser Water In [W Models] |
| 5. Electrical Connection | 8. Channel Skids |

VENTILATION PANELS

Recommend 3 ft. clearance at front for service and 18 in. clear space opposite all ventilation panels.

REMOVABLE SERVICE PANELS

Front & rear on all models

CHANNEL SKIDS

Channel skids project 2" [5 cm] front and rear. Center of mounting holes located 6" [15 cm] from chiller end and 1" [2.5 cm] from chiller edge front and rear. Skids add 2" [5cm] to overall height.

STANDARD OPERATING CONDITIONS

OUTDOOR AMBIENT
-20° to 100°F [-29° to 38°C]

OPTIONAL OPERATING CONDITIONS


OUTDOOR AMBIENT
Up to 110°F [43°C]
Up to 120°F [49°C]
Down to -30°F [-34°C]

NOTE: Higher ambient options may affect unit dimensions.

REMOTE CONDENSER

AR model furnished complete w/controls for operating in ambient temperatures to minus 20°F [-29°C]. Connections for remote condenser are at right end of chiller cabinet.


STANDARD MODELS: Suffix AR and W



GPM - CHILLER COOLING CAPACITY

CHILLER MODEL NUMBER	MAKE UP WATER	CHANGE IN TEMPERATURE THROUGH CHILLER				
		5°F	10°F	20°F	30°F	40°F
PC-8000-860	90°F	365	181	88	55	36
	80°F	361	177	82	48	30
	70°F	345	165	72	39	26*
	60°F	313	145	59	35*	21*
	50°F	265	118	52*	28*	—
	40°F	229*	104*	43*	—	—

* Agitation pump required



* For outlet temperatures below 34°F - use appropriate antifreeze