

# 107-16-HL-VP-LS

## Vandal Proof, High/Low Drinking Fountain with Cane Skirt



107-16-HL-VP-LS  
Illustration only.

### FOUNTAIN SPECIFICATIONS

#### FOUNTAIN MATERIAL – 16 gauge

- |  |  |
|--|--|
| <input type="checkbox"/> Stainless Steel | <input type="checkbox"/> Bronze            |
| <b>FINISH</b>                            | <b>FINISH</b>                              |
| <input type="checkbox"/> Satin [S]       | <input type="checkbox"/> Satin [S]         |
| <input type="checkbox"/> Mirror          | <input type="checkbox"/> Mirror            |
|  | <input type="checkbox"/> Statuary Bronze   |
|  | <input type="checkbox"/> Oil Rubbed Bronze |

#### COVER PLATE MATERIAL – 16 gauge

- ☐ Same material and finish as fountain bowl  
☐ Stainless steel with powder coat color \_\_\_\_\_  
☐ Different material and/or finish \_\_\_\_\_

#### FOUNTAIN CONTROL OPTIONS

- ☐ Separate "SOFT TOUCH" button valve [S]\*   
☐ Integral "PUSH BUTTON" valve  
☐ Integral "EASY TOUCH" lever valve

*NOTE: Finish to match bowl except stainless steel  
 "Soft Touch" valve is only available in mirror.*

#### LOW FOUNTAIN LOCATION

- ☐ Left [S] ☐ Right

#### PANEL OPTIONS

- ☐ ACCESS PANEL 6" H [S] or specify \_\_\_\_\_ in.  
 Finish matches cover plate.

### VANDAL-PROOF FEATURES

- Tamper-resistant set screw secures bubbler to fountain
- Security panels installed under bowl and bottle filler support arms with tamper-resistant screws
- Bottle filler over low fountain with "Soft Touch" valve [S]\* on arm
- Cane skirt for ADA Compliance in certain states

### OTHER OPTIONS

#### "HANDS-FREE" SENSOR ACTIVATION

Includes [4] AA lithium batteries with approximately 400,000 activation cycles. Features automatic shutoff [30 second] – helps prevent vandalism and water waste.

- ☐ On high fountain bubbler  
☐ On vandal-proof bottle filler  
☐ Bottle counter with digital display of approximate number of bottles saved through fountain usage

Bottle rest under bottle filler and 6" access panel are standard with sensor activated option. (Finish matches cover plate.)

\*ADA compliant, less than [5] lbs force to activate.

[S] = STANDARD

## 107-16-HL-VP-LS Installation Instructions

27" MINIMUM FROM BOTTOM OF MOUNTING PLATE  
 TO FINISHED FLOOR EQUALS  
 33-1/4" TO LOW BUBBLER SPOUT

