

# HF-RFK-HL

## "Hands Free" Sensor Retrofit Kit for High/Low Fountain



Model HL-HF-RFK Illustration shown with "Hands Free" sensors under both bowls and optional "Hand with Sensor" label

### Features

"Hands Free" sensor and components installed in access panel below fountain. Sensor activates when hand or body is within range.

- Includes two: sensors, solenoid valves, battery packs, flow-through regulators and circuit boards to adjust sensor distance
- [8] lithium AA batteries provided, runs for approximately 400,000 activation cycles
- Automatic shutoff after 30 seconds
- Helps prevent germ transmission and water waste
- Fits any high/low fountain model

### Labels\* (Choose one or both [S]):



\*Adhere to the fountain cover plate

### Sensor Location:

- Left Bowl     Right Bowl     Both Bowls

### Access Panel Finish Options

#### Stainless Steel [S]:

- Satin [S]     Mirrored  
 Powdercoat: \_\_\_\_\_

#### Bronze:

- Satin     Statuary  
 Mirrored     Oil-Rubbed


[S] = Standard

Model HF-RFK-HL Drawing


Dimensions in drawing subject to options selected.

"Hands Free" components are factory-assembled in electrical boxes mounted by installer to blocking under existing mounting plate


### Top View



### Front View



### Side View



The kit includes two flow-through regulators that will replace the button activated regulator in the existing fountain

See **SOFT TOUCH INSTALL [EB]** for instructions on replacing and adjusting the regulator

Existing Fountain Dimensions - Customer Fills Out	
W - Width of Fountain	D - Depth of Fountain

Retrofit Access Panel Dimensions - Filtrine Fills Out	
W <sub>RFK</sub> - Width of Access Panel	D <sub>RFK</sub> - Depth of Access Panel