

107-16-HL

Non-Recessed, High/Low Drinking Fountain



Fountain bowl and cover plate shown in standard stainless steel satin finish with "Soft Touch" button valves*, bubblers* and lever-handled bottle filler* in mirror finish

*"Hands Free" option available

Dimensions in drawing subject to options selected.

Features

- [2] 16" diameter, 16 ga. fountain bowls
- No plastic parts
- 100% made in the USA
- Manufactured with lead-free materials
- Integral drain in bowl for ease of cleaning
- $\frac{1}{4}$ " steel support arm and wall bracket capable of supporting 500 lbs.
- Cover plate and optional access panel to match bowl finish or choose from unlimited powder coat colors
- Options include vandal proof bubblers, sensor activation, bottle fillers, bottle counters, finishes, cane aprons and more...

Recommended Add-on's


Chiller

Equip your fountain with a Filtrine point-of-use or remote chiller to cool your drinking water. We can help you select the most economical chiller model to fit your demand.

Purifier

Ensure that your drinking water is of the highest quality by adding a Filtrine Taste Master[®] purifier cabinet underneath the fountain or a remote purification system serving all fountains in the building.


Top View



See Options Page for Bubbler Options


Front View

See Options Page for Bottle Filler Types



Select Low Fountain Location
☐ Left [S] ☐ Right

Side View



For options, finishes and more see page 2



Filtrine Drinking Water Non-Recessed Fountain Options


[S] - Standard
 - ADA compliant

☐ Optional Access Panel

☐ 6" Standard Height ☐ Other Height _____ in

Material: _____
 Finish: _____
 Color: _____

Easy Install
 Mounting
 Brackets
 Included



- Includes mounting brackets for simple wall installation.

☐ Optional Vandal Proof Bottle Filler (Choose only one optional filler)

☐ "Soft Touch" Valve ☐ Sensor Activation*

☐ Bottle Rest - Located above lowest bowl for reduced splash and one handed operation

☐ Bottle Counter - Digital display of approx. number of bottles saved through fountain usage
Note: Only available with sensor activation



- Mounted 10" above lowest fountain bowl.
- Comes standard with bottom security panel assembled with tamper proof screws.
- Requires larger cover plate and mounting plate.
- Supply plumbing and mounting tongue for filler provided by Filtrine.

*Not available with sensor activated bubbler on same bowl.

☐ Optional Integral "Push Back" Lever Bottle Filler (Choose only one optional filler)

- Mounted 10" above lowest fountain bowl.
- Requires larger cover and mounting plates.
- Easy-to-use stainless steel "push back" lever.
- Supply plumbing and mounting fitting for filler provided by Filtrine.



Bubbler Controls


☐ Optional Tamper Resistant Screws in Bubbler and Button (if applicable)



☐ "Easy Touch" Lever Valve



☐ "Push Button" Valve



☐ "Soft Touch" Button Valve [S]

☐ Optional Fountain Sensor Activated Bubbler*



"Hands Free" Sensor Activator


- Uses 4x -AA lithium batteries (included), runs approximately 400,000 activation cycles*
- Features automatic shutoff (30 sec).
- Helps prevent germ transmission, vandalism and water waste.

*120/60/1 voltage available

☐ Optional Security Panel

16 ga. Plate Secured with Tamper-Resistant Screws for Added Security

4x-Tamper Resistant Screws



Fountain Finish (Check One)

☐ Satin Stainless [S] ☐ Mirrored Stainless ☐ Powder Coat _____ ☐ Satin Bronze ☐ Mirrored Bronze ☐ Statuary Bronze ☐ Oil-Rubbed Bronze

Optional Cover Plate Finish (Check One)

☐ Satin Stainless [S] ☐ Mirrored Stainless ☐ Powder Coat _____ ☐ Satin Bronze ☐ Mirrored Bronze ☐ Statuary Bronze ☐ Oil-Rubbed Bronze

Stainless




Satin Stainless Steel [S]




Mirrored Stainless Steel

Bronze



Satin Bronze



Mirrored Bronze



Oil Rubbed Bronze




Statuary Bronze



Model 107-16-HL Drinking Water Installation Drawing

Mounting Plate Details (Front)



Approximate Rough-In Dimensions (hatched, left)


Model	Height	Width
Standard Plate	10 1/2"	8"
Bottle Filler Plate	20 1/2"	8"

Approximate Access Panel Rough-In Dimensions (outlined, left)

Model	Height	Width
Standard Panel	5 1/2" *	30 1/2"


Note: All views shown are for typical installation of 107-16-HL. Views, dimensions and diagrams may change for specific installation requirements.

Exploded On-Wall Installation View 107-16-HL with Access Panel




Two Methods for Mounting Model 107-16-HL to Wall

On-wall Mounting Detail With Cover Plate




Behind-wall Mounting Detail Without Cover Plate



Typical Assembly Instructions (Always Install Per Local Code)

1. Cut rough opening as shown above and install blocking or fixture carrier as required to support the assembly.
2. If optional access panel was ordered cut a separate rough opening (table, top right) extending below the fountain mounting plate.
3. Run drain pipe to center of openings on mounting plate and install drain trap in wall per local code.
4. Run supply water line with service valve, if necessary.
5. If optional bottle filler is included with order, attach piping assembly provided by Filtrine to the back side of the mounting plate with two screws and rubber gasket for standard bottle filler and flare connection for vandal proof bottle filler.
6. Fasten mounting plate over rough opening with 5/16" countersunk lag bolts with bottom of plate 26" above the floor to meet ADA fountain height requirement of 34 1/4" to the bubbler spout.
7. Install cover plate over the mounting plate for on-wall installations. Cover plate not required for in-wall installation.
8. Slide each fountain and vandal proof bottle filler arm (if ordered) over the horizontal tongues protruding from the mounting plate and fasten arms with set screws pushing slightly against the cover plate or finished wall.
9. Connect drain line to slip coupling and connect water connection.
10. If your model includes the access panel, measure, mark and install the included "L" brackets with #8-32 screws and align panel to cover plate with alignment pins.

Access Panel Mounting Brackets Installation Details



Typical Drain Plumbing Detail (In-Wall Plumbing Provided By Others, Install Per Local Code)

