

Model FCC-90MOD-HL

ADA COMPLIANT High/Low Fountain with Chiller/Purifier



STAINLESS STEEL FOUNTAIN

FOUNTAIN & COVER PLATE FINISH

☐ Satin ☐ Mirror ☐ Powder Coat

BUBBLER FINISH

☐ Mirror [S] ☐ Satin

BRONZE FOUNTAIN

FOUNTAIN & COVER PLATE FINISH

☐ Satin ☐ Mirror
☐ Statuary ☐ Oil rubbed

BUBBLER FINISH

☐ Satin [S] ☐ Mirror
☐ Statuary ☐ Oil rubbed

BUBBLER: SPECIFY

- ☐ Separate "Soft Touch" button valve [S]
- ☐ Integral push button valve
- ☐ Integral "Easy Touch" lever valve
- ☐ Separate Side Mount lever valve

BUBBLER: VANDAL PROOF [O]

- ☐ Secured to fountain with vandal proof screws

"HANDS-FREE" PHOTOCELL ACTIVATION [O]

- ☐ Includes [4] Lithium AA batteries – approx. 400,000 activation cycles. 30 sec. automatic shutoff helps prevent vandalism and water waste

GOOSE NECK BOTTLE FILLER: PUSH BUTTON [O]

- ☐ Mounted on low fountain deck

GOOSE NECK BOTTLE FILLER: LEVER VALVE [O]

- ☐ Mounted on low fountain deck

SECURITY PANEL ON BOTTOM OF FTN [O]

- ☐ Secured with vandal proof screws

LOW FOUNTAIN LOCATION

- ☐ Left [S] ☐ Right

TASTEMASTER PURIFIER [WATER IN: 1/4" FPT]

MODEL: TM1-0.5

HOUSING: Food grade poly liner with stainless steel shell.

ELEMENT: Carbon block removes particles, organic odors and tastes, chlorine odor and taste and waterborne pathogens

IN-WALL CHILLER MODEL: 56A

COOLING CAPACITY: 6 gph at 50°F

STORAGE: 2 gal, insulated stainless steel tank

REFRIGERANT: HFC R134a "Ozone Safe"

ELECTRICAL: 115/60/1 [S] _____ [O]

27" MINIMUM FROM BOTTOM
OF MOUNTING PLATE TO
FINISHED FLOOR EQUALS
33-1/4" TO LOW BUBBLER SPOUT

[S] = STANDARD / [O] = OPTIONAL

Reference information... contact Filtrine for quote or submittal

